



W30ZA 9.0" BATTERY COMPARTMENT HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH CLASS II FORKS
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 4.0" x 2.8" POLY LOAD WHEELS

24 Volt

9.0" Battery Compartment

Minimum Battery Weight - 400lbs

OEC/ID	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			STD CRG	SIDE SHIFT	STD CRG		SIDE SHIFT	
			LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage								
37"	72.0	104.0	3000	2800	104.0	3000	104.0	2800
	77.0	114.0	3000	2800	114.0	3000	114.0	2800
	83.0*	126.0	3000	2800	126.0	3000	126.0	2800
	92.0	144.0	2800	2600	132.0	3000	132.0	2800
43"	72.0	104.0	3000	2800	104.0	3000	104.0	2800
	77.0	114.0	3000	2800	114.0	3000	114.0	2800
	83.0	126.0	3000	2800	126.0	3000	126.0	2800
	92.0	144.0	3000	2800	144.0	3000	144.0	2800
49"	72.0	104.0	3000	2800	104.0	3000	104.0	2800
	77.0	114.0	3000	2800	114.0	3000	114.0	2800
	83.0	126.0	3000	2800	126.0	3000	126.0	2800
	92.0	144.0	3000	2800	144.0	3000	144.0	2800

3-Stage								
37"	72.0	157.0	3000	2800	157.0	3000	157.0	2800
	77.0*	172.0	3000	2800	172.0	3000	172.0	2800
	83.0	190.0	2000	1800	172.0	3000	172.0	2800
43"	72.0	157.0	3000	2800	157.0	3000	157.0	2800
	77.0	172.0	3000	2800	172.0	3000	172.0	2800
	83.0	190.0	3000	2800	190.0	3000	190.0	2800
49"	72.0	157.0	3000	2800	157.0	3000	157.0	2800
	77.0	172.0	3000	2800	172.0	3000	172.0	2800
	83.0	190.0	3000	2800	190.0	3000	190.0	2800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 126" (3 200 mm) (2-Stage) or 172" (4 368 mm) (3-Stage) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834