



W30ZC HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 42 INCH CLASS II FORKS

CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 10.0" x 6.0" POLY LOAD WHEELS

24 Volt

13.4" Battery Compartment

Minimum Battery Weight - 900lbs

MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
		STD CRG	SIDE SHIFT	STD CRG		SIDE SHIFT	
		LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage							
72.0	104.0	3000	2800	104.0	3000	104.0	2800
77.0	114.0	3000	2800	114.0	3000	114.0	2800
83.0	126.0	3000	2800	126.0	3000	126.0	2800
92.0	144.0	3000	2800	144.0	3000	144.0	2800
96.0	152.0	3000	2800	152.0	3000	152.0	2800
3-Stage							
72.0*	157.0	3000	2800	157.0	3000	157.0	2800
77.0	172.0	2900	2700	157.0	3000	157.0	2800
83.0	190.0	2700	2500	157.0	3000	157.0	2800
92.0	217.0	2500	2300	157.0	3000	157.0	2800
96.0	229.0	2000	1800	157.0	3000	157.0	2800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 157" (3 988 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834