



W30ZR (2 STAGE MAST) HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH CLASS II FORKS
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 3.4" x 2.8" POLY LOAD WHEELS

24 Volt

13.5" Battery Compartment

Minimum Battery Weight - 800lbs

ID/OEC	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			STD. CRG.	SIDE SHIFT	CARRIAGE		SIDE SHIFT	
			LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage								
35"	72.0	101.0	3000	3000	101.0	3000	101.0	3000
	77.0	111.0	3000	3000	111.0	3000	111.0	3000
	83.0*	123.0	3000	2800	123.0	3000	123.0	2800
	92.0	141.0	2800	2600	130.0	3000	130.0	2800
37"	72.0	101.0	3000	3000	101.0	3000	101.0	3000
	77.0	111.0	3000	3000	111.0	3000	111.0	3000
	83.0	123.0	3000	2800	123.0	3000	123.0	2800
	92.0	141.0	2800	2600	130.0	3000	130.0	2800
41"	72.0	101.0	3000	3000	101.0	3000	101.0	3000
	77.0	111.0	3000	3000	111.0	3000	111.0	3000
	83.0	123.0	3000	2800	123.0	3000	123.0	2800
	92.0	141.0	2800	2600	130.0	3000	130.0	2800
43"	72.0	101.0	3000	3000	101.0	3000	101.0	3000
	77.0	111.0	3000	3000	111.0	3000	111.0	3000
	83.0	123.0	3000	2800	123.0	3000	123.0	2800
	92.0	141.0	2800	2600	130.0	3000	130.0	2800
49"	72.0	101.0	3000	3000	101.0	3000	101.0	3000
	77.0	111.0	3000	3000	111.0	3000	111.0	3000
	83.0	123.0	3000	2800	123.0	3000	123.0	2800
	92.0	141.0	2800	2600	130.0	3000	130.0	2800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 123" (3 124 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834