



# W30ZR (3 STAGE MAST) HIGH LIFT SHEETS

**HYSTER®**

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER  
EQUIPPED WITH 42 INCH CLASS II FORKS  
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 3.4" x 2.8" POLY LOAD WHEELS

24 Volt

13.5" Battery Compartment

Minimum Battery Weight - 800lbs

| ID/OEC  | MFH   | OALH  | CAPACITY @ MFH |            | LIFT HEIGHT @ MAX CAPACITY |      |             |      |
|---------|-------|-------|----------------|------------|----------------------------|------|-------------|------|
|         |       |       | STD. CRG.      | SIDE SHIFT | CARRIAGE                   |      | SIDE SHIFT  |      |
|         |       |       | LOAD           | LOAD       | LIFT HEIGHT                | LOAD | LIFT HEIGHT | LOAD |
| 3-Stage |       |       |                |            |                            |      |             |      |
| 35"     | 73.0* | 149.0 | 2800           | 2600       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 78.0  | 164.0 | 2700           | 2500       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 83.0  | 179.0 | 2500           | 2300       | 130.0                      | 3000 | 130.0       | 2800 |
| 37"     | 73.0  | 149.0 | 2800           | 2600       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 78.0  | 164.0 | 2700           | 2500       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 83.0  | 179.0 | 2500           | 2300       | 130.0                      | 3000 | 130.0       | 2800 |
| 41"     | 73.0  | 149.0 | 2800           | 2600       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 78.0  | 164.0 | 2700           | 2500       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 83.0  | 179.0 | 2500           | 2300       | 130.0                      | 3000 | 130.0       | 2800 |
| 43"     | 73.0  | 149.0 | 2800           | 2600       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 78.0  | 164.0 | 2700           | 2500       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 83.0  | 179.0 | 2500           | 2300       | 130.0                      | 3000 | 130.0       | 2800 |
| 49"     | 73.0  | 149.0 | 2800           | 2600       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 78.0  | 164.0 | 2700           | 2500       | 130.0                      | 3000 | 130.0       | 2800 |
|         | 83.0  | 179.0 | 2500           | 2300       | 130.0                      | 3000 | 130.0       | 2800 |

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

\*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 149" (3 784 mm) is a high lift.

**HYSTER COMPANY \* 1400 SULLIVAN DRIVE \* GREENVILLE, NC 27834**

Part No.: W20-30ZR/HLS

04/10/03