



W40ZA 13.5" BATTERY COMPARTMENT HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER

EQUIPPED WITH 42 INCH CLASS II FORKS

CAPACITIES BASED UPON 10.0 x 5.0 POLY DRIVE TIRE & 4.0" x 2.8" POLY LOAD WHEELS

24 Volt

13.5" Battery Compartment

Minimum Battery Weight - 600lbs

OEC/ID	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			STD CRG	SIDE SHIFT	STD CRG		SIDE SHIFT	
			LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage								
37"	72.0	100.0	4000	3800	100.0	4000	100.0	3800
	77.0	110.0	4000	3800	110.0	4000	110.0	3800
	83.0*	122.0	4000	3800	122.0	4000	122.0	3800
	92.0	140.0	3000	2800	132.0	4000	132.0	3800
43"	72.0	100.0	4000	3800	100.0	4000	100.0	3800
	77.0	110.0	4000	3800	110.0	4000	110.0	3800
	83.0	122.0	4000	3800	122.0	4000	122.0	3800
	92.0	140.0	4000	3800	140.0	4000	140.0	3800
49"	72.0	100.0	4000	3800	100.0	4000	100.0	3800
	77.0	110.0	4000	3800	110.0	4000	110.0	3800
	83.0	122.0	4000	3800	122.0	4000	122.0	3800
	92.0	140.0	4000	3800	140.0	4000	140.0	3800

3-Stage								
37"	72.0*	153.0	4000	3800	153.0	4000	153.0	3800
	77.0	168.0	3200	3000	153.0	4000	153.0	3800
	83.0	186.0	2200	2000	153.0	4000	153.0	3800
43"	72.0	153.0	4000	3800	153.0	4000	153.0	3800
	77.0	168.0	4000	3800	168.0	4000	168.0	3800
	83.0	186.0	3000	2800	168.0	4000	168.0	3800
49"	72.0	153.0	4000	3800	153.0	4000	153.0	3800
	77.0	168.0	4000	3800	168.0	4000	168.0	3800
	83.0	186.0	3000	2800	168.0	4000	168.0	3800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 122" (3 098 mm) (2-Stage) or 153" (3 886 mm) (3-Stage) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834