



W40ZC HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH CLASS II FORKS
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 10.0" x 7.0" POLY LOAD WHEELS

24 Volt

13.4" Battery Compartment

Minimum Battery Weight - 900lbs

OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
		STD CRG	SIDE SHIFT	STD CRG		SIDE SHIFT	
		LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage							
72.0	100.0	4000	2800	100.0	4000	100.0	3700
77.0	110.0	4000	2800	110.0	4000	110.0	3700
83.0	122.0	4000	2800	122.0	4000	122.0	3700
92.0	140.0	4000	2800	140.0	4000	140.0	3700
96.0	148.0	4000	2800	148.0	4000	148.0	3700
3-Stage							
72.0*	153.0	4000	3700	153.0	4000	153.0	3700
77.0	168.0	3900	3600	153.0	4000	153.0	3700
83.0	186.0	3500	3200	153.0	4000	153.0	3700
92.0	213.0	2500	2200	153.0	4000	153.0	3700
96.0	225.0	2000	1700	153.0	4000	153.0	3700

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 153" (3 886 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834